



GENERAL EQUIPMENT INFORMATION

| ITEM | DESCRIPTION | MAKE | MODEL | QTY. |
|------|--------------------|-----------------|-----------------------------|------|
| A | CHOKE VALVES | T3 ENERGY | 4 1/8" 10M FC MANUAL | 6 |
| B | CHOKE VALVES | T3 ENERGY | 2 1/8" 10M FC MANUAL | 1 |
| C | DOWNSTREAM VALVES | T3 ENERGY | 4 1/8" 5M FC MANUAL | 2 |
| D | TRANSMITTER FLANGE | T3 ENERGY | 2-1/16" 10M | 1 |
| E | STUDDED BLOCK | T3 ENERGY | (4) 4 1/8" x (1) 2 1/8" 10M | 1 |
| F | ADJUSTABLE VALVES | T3 ENERGY | 3 1/8" 10M MANUAL | 2 |
| G | BALL VALVES | FORCE | 6" W/ 4" THROAT 285-PSI | 2 |
| H | DSA's | T3 ENERGY | 4 1/8" 10M x 3 1/8" 10M | 2 |
| I | SPACER SPOOLS | T3 ENERGY | 4 1/8" 5M x 3 1/8" 10M | 2 |
| J | BUFFER CHAMBERS | SHOP BUILT | 10" SCH 160 (10 3/4" OD) | 2 |
| K | SEPARATOR | LEDET'S WELDING | 4'OD x 20'L (1/2" Wall) | 1 |
| L | | | | |
| M | | | | |

THIS DRAWING IS OWNED BY AND CONTAINS PROPRIETARY INFORMATION OF CACTUS DRILLING COMPANY, L.L.C. IT IS CONDITIONALLY LOANED AND IS TO BE RETURNED UPON COMPLETION OF WORK OR UPON EARLIER REQUEST. THE BORROWER BY RECEIVING IT HAS AGREED NOT TO REPRODUCE NOR TO COPY IT IN WHOLE OR IN PART NOR TO FURNISH INFORMATION FROM IT TO OTHERS NOR TO MAKE ANY USE OF IT OR THE INFORMATION CONTAINED THEREIN EXCEPT FOR OR UNDER SPECIFIC LICENSE FROM CACTUS DRILLING COMPANY, L.L.C.

| SYM | DATE | REVISION | BY |
|-----|------|----------|----|
| | | | |

| | | | |
|--|--------------|----------------|----------------|
| TOLERANCE UNLESS OTHERWISE SPECIFIED DIMENSIONS IN INCHES | | CUSTOMER INFO: | |
| DECIMAL | DIMENSION | FILE: | R-166_PRFL.dwg |
| X.X | ±.1 | DWG BY: | J.D.L. |
| X.XX | ±.06 | CHK BY: | |
| X.XXX | ±.010 | APP BY: | |
| ANGLES | ± .5 DEGREES | SCALE: | NTS |
| ACAD FILE: CAC166-A-006-00-RO | | | |

CACTUS Drilling Co., L.L.C.
Oklahoma City, OK, U.S.A.
Tel: 405-577-5347 Fax: 405-577-9306

TITLE:
**RIG 166
PRESSURE-FLOW**

SIZE B CAC166-A006 SHEET 1/1