



70'
160' —●— 165'
100'
(Well Position "A")
MINIMUM AREA CLEARANCE

NOTE
Required clearance to the East increases with number of wells drilled

THIS DRAWING IS OWNED BY AND CONTAINS PROPRIETARY INFORMATION OF CACTUS DRILLING COMPANY, L.L.C. IT IS CONDITIONALLY LOANED AND IS TO BE RETURNED UPON COMPLETION OF WORK OR UPON EARLIER REQUEST. THE BORROWER BY RECEIVING IT HAS AGREED NOT TO REPRODUCE NOR TO COPY IT IN WHOLE OR IN PART NOR TO FURNISH INFORMATION FROM IT TO OTHERS NOR TO MAKE ANY USE OF IT OR THE INFORMATION CONTAINED THEREIN EXCEPT FOR OR UNDER SPECIFIC LICENSE FROM CACTUS DRILLING COMPANY, L.L.C.

TOLERANCE UNLESS OTHERWISE SPECIFIED DIMENSIONS IN INCHES		CUSTOMER INFO:	
DECIMAL	DIMENSION	FILE:	R-103_DS_3MP3GEN.dwg
CONCENTRICITY	±.1	DWG BY:	IJA
X.X	±.06	CHK BY:	
X.XX	±.010	APP BY:	
X.XXX	±.005		
ANGLES	±.5 DEGREES		
SYM	DATE	REVISION	BY
			ACAD FILE: CAC103-A-001-00-RO

		Oklahoma City, OK, U.S.A. Tel: 405-577-5347 Fax: 405-577-9306	
TITLE: RIG 103 Drill Site		SCALE: NTS	
SIZE A	CAC103-A001	SHEET 1/1	